




Serie - K



Model	A	B	C	L	H
PK043	130.0mm	106.2mm	39mm	119.0mm	93.0mm
PK070	203.5mm	149.0mm	33mm	192.0mm	138.5mm
PK100	278.1mm	212.1mm	42.5mm	259.5mm	201.5mm

Power Supply


⚠ Powered by a Low Voltage / Limited Energy power source.



⚠ Do not open the rear cover of the panel when power is applied.


⚠ Ensure that the power supply has enough power capacity for the operation of the equipment.

Function View




- 1 Front Function Key (only for PK070/100)
- 2 Power connector
- 3 COM1/COM3 9Pin Female
- 4 USB Client
- 5 Ethernet Port
- 6 USB Host

Installation Drawing



Fix Screw



⚠ Screw each fixing screw until the bezel corner gets in contact with the panel.

Dispose of batteries

Model	CR 2032 (Removable)
System	Manganese dioxide-Li/Organic Electrolyte
Nominal Voltage	3V
Nominal Capacity	220mAh
Nominal Discharge Current	0.2 mA
Operating Temperature Range	-20 to +85(C)
Weight	3.0 g
Dimensions	
Diameter	20.5mm
Height	3.2 mm
UL Recognition	MH 12568

Battery

Maxcell/Panasonic 3V 220mAh Lithium Coin Battery type.

⚠ Dispose of batteries according to local regulations.

Pin Assignment of Serial Port

COM1/COM3 9Pin Female / COM1/COM3 9Pin			
Pin	Com1	Pin	Com3
1	RS-422 TXD+ / RS-485+	7	RS-232 TXD
2	RS-232 RXD	8	RS-232 RXD
3	RS-232 TXD	5	GND
4	RS-422 RXD+		
5	SG		
6	RS-422 TXD- / RS-485-		
9	RS-422 RXD-		

The products have been designed for use in an industrial environment in compliance with the 2004/108/EC directive.

The products have been designed in compliance with:

EN 61000-6-2	EN 61000-4-2
EN 61000-6-4	EN 61000-4-3
	EN 61000-4-4
	EN 61000-4-5
	EN 61000-4-6
	EN 61000-4-8
	EN 61000-4-11

The installation of these devices into the residential, commercial and light-industrial environments are allowed only in the case that special measure are taken in order to get the conformity to IEC-61000-6-3

Reproduction of the contents of this copyrighted document, in whole or part without written permission of Cermate Technologies Inc., is prohibited.